

Mounting Instructions for Older Models

Scope of delivery

Your delivery includes the following individual parts:

- 1x terminal
- 1x charging cable
- 1x NFC reader

For mounting, you will also need the following:

- a Phillips screwdriver
- a LAN cable or a Wi-Fi connection at the desired installation location

1. Remove the cover

Turn the terminal over and remove the screws marked in the illustration. Detach the cover from the device in order to mount the NFC reader - the cover itself is not needed afterward. Your device may already be delivered without a cover. In this case, you can skip this step.

2. Mount the NFC reader

1. Mount the NFC reader using the screwdriver.
2. Then connect the NFC reader to the tablet using the supplied cable.

3. Connect the power supply

1. Unscrew the screw at the bottom left (as seen from the back) of the kiosk. You can now remove the small cover.
2. Then connect the power cable to the terminal.
3. Reattach the small cover.
4. Make sure that the connections are occupied as shown in the following illustration.

4. Establish an internet connection

The booking terminal requires an internet connection. You can establish it using a LAN cable or Wi-Fi.

- Internet via LAN cable: Connect the LAN cable to the socket provided for it on the booking terminal.
- Internet via Wi-Fi: See the Wi-Fi instructions [here](#)¹.

Your booking terminal is now ready for use. Please note that you must assign a "booking terminal admin user" and complete the registration. If the terminal has already been set up in advance, you can get started right away and skip the registration. For more information, see "Assigning a booking terminal admin user" in your Personalwolke manual.

1. </daisy/personalwolke-admin/11170-dsy.html?language=4>