TA Daily Absence Connector

With this connector, it is possible to export **daily absences** for a defined *selection of persons* over a *specific period*.

Use Cases

- Export of daily absences to an export file
- Automatic creation of project time bookings (unproductive project times) based on absences in the time system

Configuring the Connector

- **Parent connector**
- **Name**
- **Data flow direction:**
  Data source
- **Description**
- **Time and attendance system:**
  Interflex IF6020, Interflex IF6040, or Webdesk time evaluation. This determines which absence reasons are available for selection; when it is changed, the list of absence reasons is cleared.
- **Do not export 0.0 values:**
  Only persons and days where at least one account has a value other than 0.0 are exported.
- **One absence reason per page:**
  If multiple absence reasons are defined, only one absence reason is shown per person and date in the result. If, for example, 4 absence reasons are defined, there are 4 pages per person and date in the result!
- **Absence reasons**
  - Absence reason
  - Column name (prefilled with the name of the absence reason when it is selected)
  - Up and down arrow
  - Delete
- **Persons**
- **Groups**
- **Clients**

Period

The period is specified via the restriction (constraint) of the connector query with the variable **referenceDate** and date values in the format yyyyMMdd, e.g., *referenceDate = '20160119'*, *referenceDate >= '20160101' and referenceDate <= '20160119'* or *referenceDate between '20160101' and '20160119'*. Without a restriction, the values of the previous day are exported. Persons without a taId are ignored.

Fields Provided

- date, firstName, lastName, taId, employeeId, person, orgUnit
- total (sum of the hours of all configured absence reasons on the day) and total_duration
- for each configured absence reason, a field with the specified column name (hours) and a field column name + "_duration" (duration object),
- or, with **One absence reason per page**, the fields absenceCode, absenceTimeValue (hours), and absenceTimeValue_duration

Felder

Name	Wert
Modul	Time & Attendance (ta)
Webdesk Actionname	taDailyAbsenceConnector
Artefakt-Typ	Connector