

Advanced functions

The advanced functions are module-specific actions, i.e. actions that:

- affect certain Webdesk modules (e.g. refresh workflow cache)
- are general actions that affect the core functionality (e.g. clear permission cache)

These functions allow **advanced administration** and **maintenance** of Webdesk EWP.

Here it is possible, for example, to clear or refresh various caches, to register certain modules, or to update the translation files.

Module-specific actions

WARNING

Module-specific actions should in principle only be carried out after consulting Workflow consultants, since they perform system-level actions in the background that can lead to problems if used incorrectly.

Refresh workflow cache

Workflow requests are temporarily stored in a cache. Clicking the button clears this cache. Example: Two workflow engines access the same database. To bring both engines into a consistent state after a change to a workflow request, it is necessary to refresh the workflow cache.

Refresh allowed actions

There are actions that, after being carried out, check whether the action may be executed at all.

Repair folder names of all menus

Persons to hierarchical group relationships consistency check

If the Webdesk data becomes inconsistent with regard to the relationship person - organizational unit (a person is assigned to more than one organizational unit at a point in time), these relationships can be corrected by this action.

Make persons to cost center group relationships singular

Depending on the parameterization of the organization structure, a singular cost center membership can be ensured retroactively for existing cost center assignments.

Reinstall reporting engine > only in connection with the reporting module;

Restart reporting engine > only in connection with the reporting module

Delete reporting engine working directories

Only in connection with the reporting module; this action deletes temporary working directories and files.

Clear groupware cache

Groupware data is temporarily stored in a so-called cache. Clicking the button clears it; data is refreshed on the next access.

Delete holiday storage of the TA connector

Holidays can be displayed in the calendar and in journal views (highlighted in color). These are defined in the annual program of the IF6020. So that these days do not have to be read out anew every time, they are kept in a cache (storage). If new holidays are now added and the holidays have already been read out for the executing person, the data is taken from the storage. (This of course briefly leads to an inconsistency of the data, which however resolves itself after some time.) With this parameter, the storage can be cleared manually and the holidays reloaded.

Reset all passwords to random values and send mails

All passwords are set to values generated by a random generator, and each of these passwords is sent in a mail to the corresponding user. A mail notification is only sent if the user has a mail address. The mail notification is defined in the system parameters.

Reset all passwords

All passwords are reset to the value specified by the password reset policy (found in the system parameters).

Repair action names of the default language ([de]...)

If incomplete translations ([de] or [en] appears in front) still occur in the default labels, they can be displayed correctly again using the parameter.

Core functionality

Delete all log entries from database

The log entries, which can be activated individually for different actions and users at different levels, are persisted in the database. Clicking this button deletes all old log entries from the database.

Clear permission cache

Permissions for certain actions are granted by the administrator to persons, groups or roles. Every time a user calls an action, it is checked whether the user has the necessary permission to execute that action. To increase the performance of this check, the permissions are stored in a cache. For new action assignments to a person, group or role to take effect, the permission cache must first be cleared by clicking the button.

Clear menu cache

The action permissions in the navigation menu are temporarily stored in a cache. Clicking the button "Clear menu cache" clears this cache. Each menu is kept in the cache for 5000 seconds before it is renewed. If a menu is not used for more than 2000 seconds, it is removed from the cache.

Reload flowscripts

With this functionality, user-defined actions that contain a flowscript controller can be reloaded so that changes in the flowscript code become active.

Create primary text modules for all actions

Default text blocks for title and label are created for the default language.

Update translation files

The translations of the text blocks are stored in an XML file in the file system of the server. Changes to text blocks, however, are only committed to the database. For changes to text blocks to take effect, the XML file and database must be brought into a consistent state by clicking the button.

Unlock all text modules

Locked text blocks cannot be overwritten. So that *ALL* text blocks can be rewritten, e.g. during a version update of Webdesk, they must first be unlocked by clicking the button.

Lock all text modules

Clicking this button locks all text blocks in the database. When updating to a newer version of Webdesk, the text blocks and their translations can thereby be protected from unintended overwriting.

Toggle layout

System action, only carry out after consulting Workflow consultants.

Reinitialize JobService

Clicking the button "Reinitialize JobService" reinitializes the entire job service and resets it to its initial values.

Start module update

Individual modules can be updated and modified individually by update scripts. These scripts are to be placed in the respective module in the package "impl.update". This package contains a readme.txt with a detailed description of how these scripts are to be placed. In addition, the property "versionNumber" in the module's applicationContext must be set to the version number of the update script. Clicking the button executes the scripts in Webdesk without the server having to be restarted.

As a rule, however, this is not necessary, since these scripts are already executed during the start of Webdesk.

Show lock controller content

The content of the lock controller is displayed. System action, only carry out after consulting Workflow consultants.

Clear lock controller

The lock controller is cleared. System action, only carry out after consulting Workflow consultants.

Registration restriction

Webdesk R3 has various areas or packages [wf, gw, po, ta,...]. At startup these are registered, if so configured (but at least once). Registration creates the actions, language blocks, update scripts, etc. occurring in the package. If this is to be carried out manually, this parameter is used. The restriction serves to avoid always having to run all actions.

NOTIZ

Registration is very computation-intensive. To avoid performance problems in Webdesk, it should not be run during business hours.

Registration mode: e.g. with extended licenses > modules are loaded without a restart. For the registration mode, the following parameters can be selected:

- complete - everything is registered
- Everything except Textmodules - everything outside the text modules is registered.
- actions and Flowscripts - only actions and flowscripts are registered.

Start registration

This action re-registers all modules of Webdesk. In the process, for each module in Webdesk:

- Actions are registered in Webdesk
- Jobs are registered
- Action flowscripts are registered
- Configurations are registered
- User-defined actions (custom actions) are synchronized
- Text blocks are registered
- Connectors are registered

Interesting insight into the progress of the registration is provided by the file \$CATALINA_HOME/webapps/webdesk3/WEB-INF/logs/log4j.log

NOTIZ

Attention: This action can take several minutes. Webdesk is not available during this time!

Felder

Name	Wert
Modul	Portal & Organisation (po)
Webdesk Actionname	po_refreshSettings.act
Artefakt-Typ	Action